

FORMED LINING FOR VEHICLE AND METHOD FOR MANUFACTURING THE SAME

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a formed lining for a vehicle, particularly, a structure of the formed lining of which a base member and a top cover member are bonded at the same time that the lining is formed.

Description of Related Art

Generally, a formed lining for a vehicle, which has a structure that a base member and a top cover member are bonded and formed at the same time has been known. For example, FIGS. 4A and 4B show a formed lining for a vehicle in earlier technology: wherein FIG. 4A is a sectional view showing a top cover member 30; and FIG. 4B is a sectional view showing a multi-layered base member 20. The formed lining for a vehicle, wherein the top cover member 30 is bonded to the multi-layered base member 20 having a hot melt film 5 on a front thereof, has been known.

The top cover member 30 has, as shown in FIG. 4A, a top cover 1, a PUF (polyurethane foam) 2 and a nylonhalf 4 which is a knitwork of nylon. The multi-layered base member 20 has, as shown in FIG. 4B, a hot melt film 5, a PA (polyamide) film

6, a PP (polypropylene) film 7, a base material 8 and a non-woven fabric 9.

The multi-layered base member 20 is heated, thereby the hot melt film 5 on the front thereof is melted, so that the multi-layered base member 20 and the top cover member 30 are bonded together.

For improving the adhesive strength between the multi-layered base member 20 and the top cover member 30, the hot melt film 5 is required to have a film thickness of approximately from 75 to 100 μm , which normally has the thickness of approximately from 15 to 75 μm .

However, as in the earlier technology, when the film thickness of the hot melt film 5 is thickened, the production cost becomes higher. Further, when the top cover member 30 is bonded to the multi-layered base member 20 to be formed into a product shape of the formed lining for a vehicle, the stress applied to the hot melt film 5 increases. Thereby the adhesive strength becomes lower, so that a warp or deformation of the formed lining for a vehicle becomes large.

The nylonhalf 4 used on the back of the top cover member 30 has differences in expansion ratio between in a longitudinal direction and in a transverse direction, so that followability of the nylonhalf 4 for the product shape of the formed lining for a vehicle is low. Accordingly, portions not having the enough adhesive strength become raised portions.

When, for example, urethane foam having a thickness of

approximately 1 to 3 mm as a cushion layer is used on the back of the top cover member 30, the adhesive strength between the top cover member 30 and the multi-layered base member 20 deteriorates.

That is, owing to the material used for the top cover member 30, the adhesive strength to the multi-layered base member 20 becomes lower.

sub D7 For improving the adhesive strength, the hot melt film is disposed on the back of the top cover member 30. However, when the multi-layered base member 20 and the top cover member 30 are bonded, the air is involved, so that it is not able to use.

SUMMARY OF THE INVENTION

sub D27 The present invention was developed in view of the above-described problems. Therefore, an object of the present invention is to provide a formed lining for a vehicle, having high adhesive strength between a base member and a top cover member and no adhesion failure by involving the air. Another object of the invention is to provide a method for manufacturing the same.

In order to accomplish the above-described object, in one aspect of the present invention, a formed lining for a vehicle, comprises: a base member comprising a film-like hot melt

adhesive on a front thereof; and a top cover member comprising a web-like hot melt adhesive on a back thereof; wherein the top cover member is bonded to the base member and the formed lining has a laminated structure.

In accordance with another aspect of the present invention, a method for manufacturing a formed lining for a vehicle, comprises the steps of: preparing a top cover member comprising a web-like hot melt adhesive laminated previously on a back thereof, and a plate-like base member comprising a thermoplastic resin and a film-like hot melt adhesive laminated previously on a front of the base member; heating the base member; setting the top cover member and the heated base member in a forming die; melting the web-like hot melt adhesive of the top cover member by heat of the base member; and forming the top cover member and the base member at the same time that the top cover member and the base member being bonded.

According to the formed lining for a vehicle, wherein the top cover member is bonded to the base member, the top cover member has the web-like hot melt adhesive on the back thereof, while the base member has the film-like hot melt adhesive on the front thereof, so that the adhesive strength between the top cover member and the base member is high. Accordingly, it is possible to apply various types of top cover member.

After the top cover member and the base member are bonded and formed, the residual stress in the adhesive layer is small, so that it is possible to prevent the deformation of the formed

lining for a vehicle.

sub D37 The top cover member has the web-like hot melt adhesive, thereby the air between the top cover member and the base member is easily discharged through the top cover member. Accordingly, it is possible to bond and form the top cover member and the base member without involving the air between them.

Further, because the web-like hot melt adhesive is disposed on the back of the top cover member, the top cover member is slid to a material placing table by the web-like hot melt adhesive layer in a pre-step prior being set to a forming machine, thereby the top cover member is easily set to the forming machine.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the invention will become more apparent from the following description taken in conjunction with the accompanying drawings wherein like references refer to like parts and wherein:

FIGS. 1A and 1B show members of a formed lining for a vehicle according to an embodiment of the invention: wherein FIG. 1A is a sectional view showing a top cover member; and FIG. 1B is a sectional view showing a multi-layered base member;

FIGS. 2A, 2B and 2C show a manufacturing process for the formed lining for a vehicle: wherein FIG. 2A is a schematically

view showing a heating process for heating the multi-layered base member; FIG. 2B is a schematically view showing a transferring process for the multi-layered base member; and FIG. 2C is a schematically view showing a press forming process for the top cover member and the multi-layered base member;

FIG. 3 is a perspective view showing a headliner assembly according to the embodiment of the present invention; and

FIGS. 4A and 4B show members of a formed lining for a vehicle in earlier technology: wherein FIG. 4A is a sectional view showing a top cover member; and FIG. 4B is a sectional view showing a multi-layered base member.

PREFERRED EMBODIMENT OF THE INVENTION

Hereinafter, a formed lining for a vehicle and a method for manufacturing the same according to an embodiment of the invention will be explained with reference to FIGS. 1A to 3.

FIGS. 1A and 1B show members of a formed lining for a vehicle according to an embodiment of the invention, FIG. 1A is a sectional view showing a top cover member 10 and FIG. 1B is a sectional view showing a multi-layered base member 20.

The formed lining for a vehicle according to the embodiment of the invention is, for example, applied to a roof lining or a headliner for a vehicle, however, it can be applied to a side lining or the like. The formed lining for a vehicle

according to the embodiment of the invention comprises the top cover member 10 and the multi-layered base member 20, which are shown in FIGS. 1A and 1B. With the formed lining, the top cover member 10 is bonded to the multi-layered base member 20.

The top cover member 10 comprises, as shown in FIG. 1A, a top cover 1, a PUF (polyurethane foam) 2, and a hot melt web 3.

The top cover 1 is made of tricot or other fabric material laminated on the front 2a of the PUF 2.

The PUF 2 is for a cushion layer for absorbing the external shock. On the front 2a thereof, the top cover 1 is laminated, while on the back 2b thereof, the hot melt web 3 is disposed.

The hot melt web 3 is an adhesive having, for example, a density of from 15 to 50 g/m² and a web-like structure, and including PA (polyamide), EVA (vinyl acetate), EEA (ethylene-ethyl acrylate copolymer), PO (polyolefin), PET (polyethylene terephthalate) or other components. The hot melt web 3 having the web-like structure has superior followability for the product shape of the formed lining for a vehicle, so that the adhesion between the top cover member 10 and the multi-layered base member 20 is improved.

Accordingly, it is possible to obtain high adhesive strength.

Sub
The hot melt web 3 melts by the heat of the heated multi-layered base member 20 to bond the top cover member 10 and the multi-layered base member 20. At this time, because the hot melt web 3 has air permeability, the air between the

Sub
DET
top cover member 10 and the multi-layered base member 20 is discharged through the hot melt web 3 to prevent involving the air.

As shown in FIG. 1B, the multi-layered base member 20 comprises a hot melt film 5, a PA (polyamide) film 6, a PP (polypropylene) film 7, a base material 8 and a non-woven fabric 9.

The hot melt film 5 is a film-like adhesive, such as PA or EVA having, for example, a film thickness of approximately from 50 to 75 μm and disposed on the PA film 6. The hot melt film 5 melts uniformly by heating the multi-layered base member 20 by a heater, so that the hot melt film 5 bonds the top cover member 10 and the multi-layered base member 20.

The PA film 6 has superior heat resistance and, for example, a film thickness of from 15 to 60 μm and which is disposed above the base material 8. When the hot melt film 5 is heated by the heater to melt, the PA film 6 prevents infiltration of the adhesive into the base material 8. The PA film 6 also has efficiency of preventing ventilation.

The plate-like base material 8 includes thermoplastic resin which is made of glass fiber and PP (polypropylene), and which is, as a roof lining, formed into a desired three-dimensional product shape through a press forming process. On the front of the base material 8, the PP film 7 is disposed, while on the back thereof, the non-woven fabric 9 is disposed.

The non-woven fabric 9 is a backing cloth manufactured

by a span bond method.

Next, the method for manufacturing the formed lining for a vehicle will be explained as follows with reference to FIGS. 2A to 2C.

As shown in FIG. 2A, the multi-layered base member 20 previously set to base member clamps 13 is heated in a heater 40, thereby the adhesive is melted uniformly. The heater 40 has an upper heater 11a and a lower heater 11b to uniformly melt the adhesive and to soften the multi-layered base member 20.

As shown in FIG. 2B, the heated and softened multi-layered base member 20 is transferred to a press forming machine 50 shown in FIG. 2C. The press forming machine 50 has a forming die comprising an upper die 12a and a lower die 12b.

The top cover member 10 is set to top cover member clamps 14. In a pre-step prior to being set to the top cover member clamps 14, the top cover member 10 is slid to a material placing table by the hot melt web 3, thereby the top cover member 10 is easily set to the clamps 14.

Then, the top cover member 10 having the hot melt web 3 and set to the top cover member clamps 14 is set between the upper and lower dies 12a and 12b, while the multi-layered base member 20 which is set to the base member clamps 13 and heated is set under the top cover member 10 set between the upper and lower dies 12a and 12b in the state that the base member 20 softens and the adhesive melts uniformly.

In this way, the clamps 14 to which the top cover member 10 is set and the clamps 13 to which the multi-layered base member 20 is set are set between the upper and lower dies 12a and 12b.

Then, the upper die 12a and the lower die 12b are put together, so that the cold press forming is performed for 20-30 seconds. At this time, the hot melt web 3 of the top cover member 10 melts by the heat of the heated multi-layered base member 20, so that the adhesive strength between the top cover member 10 and the multi-layered base member 20 is improved.

In this way, the top cover member 10 and the multi-layered base member 20 are bonded and at the same time formed into the product shape, so that the formed lining for a vehicle is manufactured. For example, a formed headliner assembly 60 as shown in FIG. 3 is manufactured. The headliner assembly or roof lining 60 as shown in FIG. 3 is shown from interior of the vehicle.

As described above, according to a formed lining for a vehicle, a multi-layered base member has a film-like hot melt adhesive on a front thereof, while a top cover member has a web-like hot melt adhesive on a back thereof, so that the adhesive strength between the top cover member and the base member is exceedingly improved. Accordingly, it is possible to apply various types of top cover member. For instance, it is possible to apply materials having inferior adhesion, such as the PUF (polyurethane foam) which is used as a cushion layer.

It is not required to thicken the film thickness of the

film-like hot melt adhesive, so that the residual stress in the web-like hot melt adhesive and the film-like hot melt adhesive after bonding is small. Accordingly, it is possible to prevent deformation of the formed lining for a vehicle.

Sub D57 The web-like hot melt adhesive is disposed on the back of the top cover member, thereby the air between the top cover member and the base member is easily discharged through the top cover member. Accordingly, it is possible to bond and form the top cover member and the multi-layered base member without involving the air between them. Therefore, it is possible to bond and form efficiently the top cover member and the multi-layered base member.

Further, because the web-like hot melt adhesive is disposed on the back of the top cover member, the top cover member is slid to a material placing table by the web-like hot melt adhesive in a pre-step prior being set to clamps for a top cover member, thereby the top cover member is easily set to the clamps.

From the foregoing description, one skilled in the art can easily ascertain the essential characteristics of this invention, and without departing from the spirit and scope thereof, can make various changes and modifications of the invention to adapt it to various usage and conditions.

The entire disclosure of Japanese Patent Application No. 11-152308 filed on May 31, 1999 including specification, claims, drawings and summary are incorporated herein by reference in

Year	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	